

Full Color Fine Pitch Led Display P1.875 Standard Resolution Indoor Light Weight

Basic Information

Place of Origin: GuangdongBrand Name: TOPLED

Certification: CE, ROHS, FCC, ISO9001, ISO14001

Model Number: indoor p1.875
Minimum Order Quantity: Negotiation
Price: Negotiation

• Packaging Details: Wooden case, flight case, honeycomb.

• Delivery Time: 15-20 Working days

Payment Terms:
L/C, D/A, D/P, T/T, Western Union,

Money Gram

• Supply Ability: 1000 SQM/Month



Product Specification

Cabinet Material: Die Casting Aluminum

Cabinet Size: 480*480mmModule Size: 240*240mm

Module Max. Current: 8A

Tube Chip Color: Full Color Module Resolution: 128*96

• Highlight: fine pitch led display, small pixel led display



More Images



Product Description

2K Resolution Video Display Function Indoor p1.875 Full Color Tube Chip Color LED Display

Product Description

- 1. Gorgeous Picture: Non-reflective screen, which brings better viewing experience.
- 2. Perfect Image: Our products use special IC for LED which owns high refresh rate and achieves no shadows
- 3. Light Weight: The body uses aluminum profile stitching weighing 5-8kg, which is light and non-corrosive.
- 4. Elegant Appearance: We adopt CNC processing technique to produce standard module and cabinet which can easily do seamless assemble.
- 5. Standard Size: We use professional buckles and standard modular panels which can snap together easily.

Specification

Name	P1.875
Pixel Pitch(mm)	1.875
Physical Density	284,444
LED Configuration	1RGB
LED type	SMD1515
Module Size	240×240
Module Resolution	128×128
Module Power Consumption	18W
Driving Mode	Constant Current IC
Scanning Mode	1/32
Horizontal Viewing Angle	140
Vertical Viewing Angle	120
Brightness	1500
Grey Scale	16bit
Refresh Rate	≥3840
Cabinet Resolution	256×256
Cabinet Max Consumption	180
Cabinet Average Power Consumption	60
Cabinet Size	480×480
Cabinet Weight(kg)	8.5KG
Cabinet Thickness	80mm
Cabinet Material	Die-casting Aluminum
Color	>16.7
Input Voltage	AC 110V~220V +/-10%
Frame Frequency	≥60
Protection Level	IP43
Working Temperature()	-40° -+65°
Storage Humidity Range(RH)	40%~60%
Life Span(H)	100,000 hours





Beijing Silk Road Enterprise Management Services Co.,LTD

