

Full Color P5 Indoor LED Video Wall 320*160mm Module VGA High Contrast

Basic Information	
• Place of Origin:	Guangdong
• Brand Name:	TOPLED
Certification:	CE, ROHS, FCC, ISO9001, ISO14001
 Model Number: 	Indoor p5
Minimum Order Quantity:	Negotiation
Price:	Negotiation
 Packaging Details: 	Wooden case, flight case, honeycomb.
 Delivery Time: 	15-20 Working days
• Payment Terms:	L/C, D/A, D/P, T/T, Western Union, MoneyGram
 Supply Ability: 	1000 SQM/Month



• Pixels:	5mm	
 Brightness: 	900cd/sqm	
 Display Function: 	Video	
 Life Span: 	100000 Hours	
Warranty:	2 Years	
 Scan Mode: 	1/16	
 Highlight: 	led video wall display, led wall panels	



More Images



Product Description

320*160mm Module VGA High Contrast Full Color P5 Indoor LED Video Wall

Our advantages are as following:

1. Excellent Project design solution

- D professional engineers for installing and maintaining guidance
 P1.5, P1.875 Small pixel pitch HD LED display factory for indoor and outdoor advertising
 CE, ROHS, FCC, CCC, ISO9001, ISO14001 qualified Manufactory
- 5. Successfully finished 1100+ cases all over the world
- 6. Free project install solution design

Parameter

Name	Parameter	
Pixel Pitch(mm)	5mm	
Physical Density	40,000	
LED Configuration	1RGB	Would you please advise your detail
LED type	SMD2121	requests on:
Module Size	320×160	

		1. the size of the screen(width and
Module Resolution	64×32	height)
Module Power Consumption	20W	the using environment
Driving Mode	Constant Current IC	the installation type(fixed or
Scanning Mode	1/16	rental)
Horizontal Viewing Angle	140	4. the content for playing(text,
Vertical Viewing Angle	140	picture or video)
Brightness	800-900	5. other detail requirements
Grey Scale	16bit	Suitable project solution would be
Refresh Rate	≥3840Hz	offered.
Cabinet Resolution	128×128	onered.
Cabinet Max Consumption	160	
Cabinet Average Power Consumption	50	
Cabinet Size	640×640	
Cabinet Weight(kg)	18kg	
Cabinet Thickness	75mm	Beijing Silk Road
Cabinet Material	Iron/Aluminum	
Color	>16.7	Enterprise Management
Input Voltage	AC 110V~220V +/-10%	Services Co.,LTD
Frame Frequency	≥60	86188888888888 andy@gmail.com
Protection Level	IP43	
Working Temperature()	-40° -+65°	Room 402.Dongbao
Storage Humidity Range(RH)	10%~90%	Building,No.19
Life Span(H)	100,000 hours	Dongbao

bighb