



## 65536 Grey Scale Perimeter Led Screen P10 Outstanding Corrosion Resistance

### Our Product Introduction

#### Basic Information

- Place of Origin: China (Mainland)
- Brand Name: Singheng
- Certification: CE RoHS UL Certifications
- Model Number: P10
- Minimum Order Quantity: 1 square meter
- Price: USD+To be negotiated+square meter
- Packaging Details: Plywood case
- Delivery Time: About 16 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 3000+square meter+per month



#### Product Specification

- Application: Video
- Warranty: 3 Years
- LED Chip: Epistar
- Refresh Rate: >1920Hz
- Grey Scale: 65536
- Max Power Consumption: 600w/sqm
- Average Power Consumption: 260w/sqm
- Screen Dimension: Customized Size
- Material: Iron Or Magnesium Alloy
- Drive Mode: 1/4 Scan
- Highlight: led perimeter board, stadium led screens

for more products please visit us on [highbrightnessleddisplay.com](http://highbrightnessleddisplay.com)

## Product Description

### Football Ground Advertising Boards Perimeter Led Screen P10 Led Banner Price

#### Product description

1. We have the most competitive prices based on all good material we use . Our quality is very repliable and we win very good reputation in the market.
2. Inner fixed reinforcement plate, tensile and shockproof, auto heat dissipation, make the operating life 10 years.
3. The perimeter Led screen cabinet has good moisture and corrosion resistance and can be used in different climate regions around the world. It can be used in temperatures ranging from -30 °C to 60 °C, even in high humidity and high salinity air environments.
4. A hemispherical soft protective cover and a soft mask are installed above and on the front of the screen to provide a good safety guarantee for the athletes and LED lights.
5. The new cabinet design meets the fence and stacking installation. It can be used in different applications for various occasions, can meet the needs of users with multiple applications.
6. The football ground advertising boards cabinet adopts a triangular door and a unique tilt angle design. Our stadium screen can adjust the tilt angle (60°~90°) of the cabinet according to different requirements, so that all the audience can see the displaying content.
7. With the high quality raw material, mature process and scale production,the quality is ensured.

#### Technical parameter of P10 Led Banner

Item	P10
Pixel Pitch	10 mm
Pixel Density	10000dot/sqm
Pixel Configuration	1R1G1B SMD3535
Module Size	320*160 mm
LED brand	Taiwai EPISTAR
Cabinet type	Closed
Module Resolution	32*16 dot
Weight	30KG/sqm
Cabinet Material	SPCC or magnesium alloy
Viewing Distance	≥10 m
Viewing Angle (Horizontal)	140°
Viewing Angle (Vertical)	120°
Refresh Rate	1920Hz
Grey Scale	65536
Brightness	≥6000cd/m2
Max Power Consumption	600 w/sqm
Average Power Consumption	260 w/sqm
Drive Mode	1/4 scan
Lifespan	≥100,000 hours
Waterproof Grade	IP65
Input Voltage	AC105-235V 50-60HZ
Celsius	-40 ~40
Humidity	10~85%RH

#### FAQ

Q1: LED display models are generally expressed in PX, such as P2 P3 P4....P8 P10.What does this mean?

A: P2 P3 P4.....P8 P10 means the pixel pitch is 2mm 3mm 4mm....8mm 10mm,which determines the number of pixels per unit area of a display. So it represents the clarity of the display. The smaller the pitch, the higher the clarity. Usually, the models of indoor full color display are P1.875,P2.5,P3,P4,P5. Outdoor full color display are P4,P5,P6,P8,P10.

Q2: How about your quality?

A: The quality of our display is excellent. We use the materials of high quality suppliers, strictly control the production process. and pass the multiple quality inspection to ensure every product is qualified.

Q3: What about the warranty?

A: Three year warranty

Q4: Can I order a sample?

A: Yes.We welcome customers to order sample to check the quality and service.



**Beijing Silk Road Enterprise Management Services Co.,LTD**



8618888888888



andy@gmail.com



highbrightnessleddisplay.com

Room 402.Dongbao Building,No.19 Dongbao Road,Songjiang,Shanghai 201613,China